

Introducing the DINGO

Vibration

Electric Vibrator

Proven worldwide in all construction environments and temperature extremes.

The 3HP 2300 Watt system designed to assure long life and absolute safety.



Electric Motor

- Drive Unit has 3 handles ergonomically located around the body and a rear handle for short drives and vertical applications.
- Easily adjustable and removable carry belt.
- Handles are designed for the operator and for added protection to the motor case.
- Durable Foam air intake filter.
- Electrical cable reinforced at the motor outlet.
- Protected and sealed on/off switch.
- Motor housing has 5 times the required protection against ground fault shorts.
- Flexible drives from 1m to 5m.
- Flexible Drive casing has anti-abrasion outer cover with integrated mesh reinforcing.
- Case reinforced at shaft coupling for added toughness.

Vibrating Heads

Vibrating heads available in four different diameters

- 1 in. - 25mm
- 1.5 in. - 38mm
- 1.9 in. - 48mm
- 2.3 in. - 58mm
- Oversized Steel Eccentric and hardened steel end.
- Double seal at shaft attachment point provided to prevent entrance of contaminants.

Flexible Shafts

- Standard Length from 3 ft to 16 ft.
- Strengthened with metallic mesh.
- Reinforced ends to protect areas receiving more intense bending.

Specifications

Model	Weight	Power	Voltage	Speed	Size
DINGO	11.9 lbs 5.4 kg	2300 w	115 V 50-60 Hz	18,000 rpm	13.5x 9x9.8 in 343x243x228 mm

Pokers	Diameter		Length		Weight		Capacity		RPM
	in	mm	in	mm	lbs	kg	y ³ /h	m ³ /h	
AX 25	1	25	11.8	300	2.2	1	11	10	14,000
AX 38	1.5	38	13.6	345	4.2	1.9	19	17	13,500
AX 48	1.9	48	14.6	370	7.5	3.4	31	28	13,500
AX 58	2.3	58	16.1	410	12.1	5.5	38	35	12,500

Flexible Shafts	Length		Weight	
	ft	mm	lbs	kg
TDX 1 - TDXE 1	3.3	1	6.6	3
TDX 1.5 - TDXE 1.5	4.9	1.5	7.7	3.5
TDX 2 - TDXE 2	6.6	2	8.8	4
TDX 3 - TDXE 3	9.8	3	11	5
TDX 4 - TDXE 4	13	4	13.2	6
TDX 5 - TDXE 5	16.4	5	15.4	7

TDXE only used with AX 25

ADVANTAGES

RESISTANCE high impact housing to protect the motor.

SAFETY double insulated motor.

SIMPLICITY easy interchanges of flexible shafts and vibrating heads.

POWERFUL compact up to 33.8 yds³/h of concrete.

LIGHTWEIGHT the unit motor weight under 12 lbs. (5.4 kg)



ADVANCED CONCRETE TOOLS

P. O. Box 1239 · Bonifay, FL 32425

800-648-0542

advancedconcretetools.com